



GruloLine



GruloKan 250 PROtect

For your own safety

GruloKan 250 PROtect offers you all the benefits of our classical rubber sewer cleaning hose **GruloKan 250**. Furthermore the yellow protection layer underneath the cover makes it easier for you to handle a high pressure hose in accordance with the requirements of working safety. As soon as the cover gets thinner – in consequence of the rough operating conditions – the yellow protection layer becomes visible and warns you that its time to change the hose. So you and your staff members are always on the safe side.

All hoses are assembled with BSP female/male and ferrules. Delivery takes place with test certificate on each assembled hose.

Technical characteristics

Temperature range: -40 °C to +70 °C

Standard Length: 60 m, 80 m, 120 m, 160 m, 180 m, 200 m, 220 m, 240 m
further lengths on request

Availability: 10 m up to 240 m | DN 32 up to 200 m

Colour: Black

Construction

Cover: NR/SBR, highly abrasion resistant, smooth

Protection layer: SBR/EPDM, yellow

Reinforcement: Twofold braided synthetic fibres

Lining: NR/SBR, black, smooth

Transfer tape: G+L Ellipse GruloKan PROtect 250 bar DN [..]

Inner-Ø mm	Inner-Ø Inch	Wall thickness mm	WP bar	BP bar	Bending radius mm	Weight/m kg	Article no.
25	1	7,50	250	625	100	0,880	10766-025
32	1 1/4	8,50	250	625	130	1,190	10766-032

Reliable, for sure!