



SuperSucker Professional | 5 m-length Suction Hose with spiral-free cuffs

Rubber spiral suction and delivery hose, spiral-free cuffs on both sides. Particularly suitable for suction and discharging of abrasive materials like sand and gravel. Wear layer with an excellent abrasion resistance in para-quality. Electrically conductive $R \leq 10^6 \Omega/m$. Delivery occurs with spiral-free cuffs, on request available with widened ends or by metre.

Technical characteristics

Temperature range: -40 °C to +80 °C

Standard Length: 5 m | further lengths on request

Electrical resistance: Cover $R \leq 10^6 \Omega/m$

Colour: Black

Construction

Cover: NR/BR, black, corrugated, fabric impressions, electrically conductive

Reinforcement: Textile cord, steel spiral, copper litz wire

Lining: NR/BR, black, smooth, electrically conductive

Wear layer: Para, black, 4 mm

| Inner-Ø mm | Inner-Ø Inch | Wall thickness mm | Cuff width mm | WP bar | BP bar | Bending radius mm | Weight/m kg | Article no. |
|---------------|-----------------|----------------------|------------------|-----------|-----------|----------------------|----------------|---------------|
| 80 | 3 1/8 | 8,00 | 150 | 5 | 15 | 240 | 3,500 | 11132-080-005 |
| 102 | 4 | 9,00 | 180 | 5 | 15 | 306 | 4,400 | 11132-102-005 |
| 127 | 5 | 9,00 | 180 | 5 | 15 | 381 | 6,800 | 11132-127-005 |
| 152 | 6 | 9,00 | 200 | 5 | 15 | 456 | 8,900 | 11132-152-005 |

Reliable, for sure!